


Aruba

Collection Inside Out 340

Technical data sheet

GENERAL		
Composition		85%PP +34%PL
Roll width		140cm
Roll length		+/-30m
Weight		780gr/m
TESTS	METHOD	RESULT / U.M.
Martindale abrasion	UNI EN ISO 12947-2	25.000 cycles
Pilling	UNI EN ISO 12945-2	4
Colour fastness to rubbing (dry)	UNI EN ISO 105 X12	4-5
Colour fastness to rubbing (wet)	UNI EN ISO 105 X12	4-5
Colourfastness to light	UNI EN ISO 105 B02 - B04	7
Colour fastness to sea / chlorinate water	UNI EN ISO 105 E02 - E03	5
Burning behaviour	UNI EN ISO 1021 part 1 IMO 2010 FTP part 7+8	pass
CERTIFICATS		
Resistant to chlorine		
100% mould and bacteria resistant, anti-allergic and anti-mite		
Does not absorb water, dirt repellent		
Thermoregulating, breathable		
Floating fiber		
OekoTex class 1 and 100% recyclable		
CERTIFICATS		
		
FR EN 1021 PART 2 OPTIONAL (with foam backing)		

CLEANING INSTRUCTIONS



EASY TO CLEAN, using water and dish wash soap



REMARKS

***INTENSIVE DOMESTIC AND CONTRACT USE ***

Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use the fabric.