

# Collection Crypton

Fabric collection

Technical data sheet Hit + Like

<b>GENERAL</b>		
Composition		100% PL
Roll width		137cm
Roll length		+/- 30m
Weight		670 gr/m
<b>TESTS</b>	<b>METHOD</b>	<b>RESULT / U.M.</b>
Repellency (water/alcohol solution + oil)	AATCC 22+193+118	80-100 (100max); 6
Hydrostatic resistance	AATCC 127 (moisture barrier)	>100cm
Bacteria resistance + fungal growth resistance (Antimicrobial Silver Ion Technology)	EN ISO 20743 AATCC 4352+30+6275	95% (+/-5%)
Piling	EN ISO 12945-2	4-5
Martindale abrasion	ASTM D 4157	+50.000 double rubs
Colourfastness to rubbing	EN ISO 105-X12	4-5 dry / 3-5 wet
Colourfastness to light	EN ISO 105 B02	>4
Burning behaviour	TB117, section E/NFPA 260/UFAC BS 5852 part 1+2	class 1, pass pass
<b>FURTHER CHARACTERISTICS</b>		
<b>ECO FRIENDLY</b> (Greenguard Gold Certified)		
<b>REACH COMPLIANT:</b> free of harmful levels of PFOS, PFOA, formaldehyde, heavy metals, phenols, phthalates, odor and skin sensitizers		
<b>MOISTURE RESISTANT</b>		
<b>LIQUID + OIL REPELLENT</b>		
<b>ODOR RESISTANT</b>		
<b>RECYCLABLE</b>		
<b>CLEANING INSTRUCTIONS</b>		
<b>EASY CLEAN</b>		
Stain resistance with water and mild detergent (1% dishwashing liquid-laundry detergent)		
<b>REMARKS</b>		
<b>***INTENSIVE DOMESTIC, INDUSTRIAL AND CONTRACT USE</b>		
Slight color differences between production batches can occur.		
The test results only apply to the samples tested.		
Buvetex can't be kept liable for inappropriate use of the fabric.		