










Collection Novara

Artificial leather

Technical data sheet

<u>GENERAL</u>		
Composition surface	88% PVC	
Composition back cloth	12% PL	
Roll width	138cm	
Roll length	+/- 30m	
Weight	670 gr/m ² (+/-10%)	
Thickness	0.9mm (+/-10%)	
<u>TESTS</u>	<u>METHOD</u>	<u>RESULT / U.M.</u>
Fastness to rubbing - dry	UNI EN ISO 105 X 12	-
Fastness to rubbing - wet	UNI EN ISO 105 X 12	-
Colour fastness to light	UNI EN ISO 105 B 02	>= 6
Colour fastness to perspiration	UNI EN ISO 105 E 04	-
Flexing endurance Bally Flex	UNI EN ISO 5402	-
Resistance to blocking	UNI EN ISO BS 3424	-
Martindale abrasion	UNI EN ISO 12947-2	>= 52.000 rubs
Anti-bacterial activity	UNI EN ISO 20743 -8.2	pass
Conformity to REACH	-	pass
Burning behaviour	BS 5852 Crib 5 CL1/IM M2 EN 1021 part 1 and 2 TB117E FAR 25.853 app F. to part 25	pass
<u>CERTIFICATS</u>		
EUROPEAN STANDARD EN 12149		
<u>GENERAL INFORMATION</u>		
		
Fireproof	Easy assembly	UV and low T° resistant
		
Long life	REACH compliant	Waterproof
		
Antibacterial	Abrasion resistant	Easy to clean

CLEANING INSTRUCTIONS

Novara is easily cleanable. Stains can be removed using standard detergents and alcohol that is properly diluted.

REMARKS

**** INTENSIVE DOMESTIC/CONTRACT USE



Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the artificial leather.