










Collection Scarlet

Artificial leather

Technical data sheet

<u>GENERAL</u>								
Composition surface		100% PVC						
Composition back cloth		100% PES						
Roll width		137cm						
Roll length		30m						
Weight		550 gr/m ²						
Thickness		1.00mm						
<u>TESTS</u>	<u>METHOD</u>	<u>RESULT / U.M.</u>						
Fastness to rubbing - dry	UNI EN ISO 11640	5						
Fastness to rubbing - wet	UNI EN ISO 11640	4/5						
Colour fastness to light	UNI EN ISO 105 B 02	6+						
Colour fastness to perspiration	UNI EN ISO 105 E 04	5						
Flexing endurance Bally Flex	UNI EN ISO 5401	>100.000						
Resistance to blocking	UNI EN ISO BS 3424	no blocking						
Martindale abrasion	UNI EN ISO 12947-2	>= 51.200 rubs						
Anti-bacterial activity	UNI EN ISO 20743 -8.2	pass						
Conformity to REACH	-	pass						
Burning behaviour	BS 5852 source 0 + 1 EN 1021-1 / EN 1021-2	pass						
<u>CERTIFICATS</u>								
ECE R NO 118 (2005) + Rev 1 (2012) annex 8								
<u>GENERAL INFORMATION</u>								
								
Fireproof	Easy upholstery	UV and low t* resistant	Long life	REACH compliant	Waterproof	Antibacterial	Abrasive resistant	Easy to clean
<u>CLEANING INSTRUCTIONS</u>								
Water and neutral soap.								
<u>REMARKS</u>								
**** INTENSIVE DOMESTIC/CONTRACT USE								

Slight color differences between production batches can occur.

The test results only apply to the samples tested.

Buvetex can't be kept liable for inappropriate use of the artificial leather.